SCHOOL AND SHUTTLE RANSPEC **BUS ROOF HATCHES**



SAFE EGRESS. PROVEN PERFORMANCE.





ADAPTABLE Low profile design adapts to wide range of roof surfaces



MADE IN THE USA Proudly manufactured in North Carolina with 35 years proven product performance



MAINTENANCE No external fasteners required for installation



WARRANTY 5 year



STRENGTH Constructed of high strength UV stable materials



Serves as a vent on hot summer days

SPECIFICATIONS

SCHOOL AND SHUTTLE ROOF HATCHES

D SHUTTLE HES			Jupi	IR VENT LATIC V	ENT OF	ints whi	The dos	RELEA	SE HANG	DIE LE ARRI LIAR ALARI LIAR ALARI LIAR CURL	ASWITC DECALS			/ /sti	/ / /%/	//	(th)	ORLO H
■ = Standard O = Optional MODEL	cotors						1757 R	ETE X	ATCR	ilin			ORCH ORCH		CHOOL	SIZ		ORLL
T1170 Series Triple Value Safety Vent II	White Light Gray Dark Gray	-	■ I	•	■	0	0	0	0		APT	LICA	ATTO:	1		31Z ■	E 5	
T1670 Series Power Safety Vent II	White Light Gray Dark Gray Beige	•	•	•	•	0	0	0	0		•	•	•	•		•		
T1970 Series Standard Safety Vent II	White Light Gray Dark Gray Beige	•		•	•	0	0	0	0					-		•		
9245 Series Pro Lo Roof Hatch	White Light Gray Dark Gray	П		-	-	0	0	0	0		•			-				-

T1170 Series / Triple Value Safety Vent II

The Triple Value Safety Vent II is a combination roof ventilator/ emergency exit that provides 5-position fresh air ventilation as well as incorporating a built in non-closeable static exhaust vent. The product also includes a simple release handle that allows the hatch to hinge open for emergency exit.

Additional Features

- Static Vent provided with one piece outer cover designed to minimize leaks
- Interchangeable with earlier Transpec models
- Available in various radiuses to fit different roof curvatures
- Available with vandal lock feature
- Constructed of high strength UV stable materials
- Available with optional adhesive sealant and reflective tape
- Meets D250 Standard for Canadian school bus

T1670 Series / Power Safety Vent II

The Power Safety Vent II provides all the features of the Triple Value Safety Vent II with the addition of an electric fan for extracting condensation. stale or hot air from inside the vehicle to improve passenger comfort.

Additional Features

- Interchangeable with earlier Transpec models
- Available in 12 and 24 volt
- Available in various radiuses to fit different roof curvatures
- Constructed of high strength UV stable materials
- Available with optional adhesive sealant and reflective tape
- Meets D250 Standard for Canadian school bus

T1970 Series / Standard Safety Vent II

The Standard Safety Vent II is a combination roof ventilator/emergency exit that provides 5-position fresh air ventilation and a simple release handle that allows the hatch to hinge open for emergency exit.

Additional Features

- Retrofits to all hatch openings
- Interchangeable with earlier Transpec models
- Available in various radiuses to fit different roof curvatures
- Constructed of high strength UV stable materials
- Available with optional adhesive sealant and reflective tape

9245 Series / Pro Lo Roof Hatch

The Pro Lo is a combination roof ventilator/ emergency exit that mounts nearly flush with the roof (0.75" above the roof). Designed to fit the roof curvature, it creates a tight seal virtually eliminating water intrusion. The hatch also incorporates a release handle allowing it to be opened as an emergency exit.

Additional Features

- Available in various radiuses to fit different roof curvatures
- Nearly flush at 0.75" above the bus
- Constructed of high strength UV stable materials
- No exterior screws for installation
- Available with vandal lock feature
 - Meets D250 Standard for Canadian school bus



EMERGENCY EXIT