Slide Away[™]

Retractable Step System



Provide drivers with a safe step system on and off the vehicle or trailer.



SLIP RESISTANT

A serrated walk surface provides superior traction with every step, regardless of weather.



EASY OPERATION

Retractable design deploys or stows in seconds.



MULTIPLE STEP OPTIONS

Available in 1, 2 or 3 step models.



3 POINTS OF CONTACT

Optional grab handle helps ensure safe trailer access.








Slide Away™

Retractable Step System









CD			$C \Lambda T$		LIC.
2L	ヒレ	IFI	CAT	IUI	V 2

	REFERENCE		A B			C	D	
	PART#	MOUNT TYPE	TOTAL WIDTH	STAIR WIDTH	TREAD DEPTH	CLOSED LENGTH	OPEN LENGTH	WEIGHT
STEP	DB0205	Weld On	27 1/4"	26 ½"	6 1/16"	11 ¹³ / ₁₆ "	16 %"	25 lbs.
1 S	DB0206	Bolt On	31 1/4"	26 ½"	6 ¹ / ₁₆ "	11 ¹³ / ₁₆ "	16 %"	30 lbs.
	HB0201	Weld On	15 1/4"	14 ½"	6 ¹ / ₁₆ "	20 ³ / ₁₆ "	33 ¹ / ₁₆ "	29 lbs.
STEP	DB0201*	Bolt On	19 1/4"	14 ½"	6 ¹ / ₁₆ "	20 ³ /16"	33 ¹ / ₁₆ "	30 lbs.
2 S	DB0204	Weld On	27 1/4"	26 ½"	6 ¹ / ₁₆ "	20 ³ /16"	33 ¹ / ₁₆ "	38 lbs.
	DB0203	Bolt On	31 1/4"	26 ½"	6 ¹ / ₁₆ "	20 ³ /16"	33 ¹ / ₁₆ "	42 lbs.
	HB0202*	Weld On	15 1/4"	14 ½"	6 ¹ / ₁₆ "	34 ³ /16"	56 5/16	44 lbs.
원	DB0202*	Bolt On	19 1/4"	14 ½"	6 ¹ / ₁₆ "	34 ³ /16"	56 5/16"	48 lbs.
3 ST	HB0203	Weld On	27 1/4"	26 ½"	6 ¹ / ₁₆ "	34 ³ /16"	56 ⁵ /16"	56 lbs.
	HB0204*	Bolt On	31 1/4"	26 ½"	6 ¹ / ₁₆ "	34 ³ / ₁₆ "	56 ⁵ /16"	60 lbs.

^{*}Available with galvanized finish

OPTIONAL REMOVEABLE GRAB HANDLE SPECIFICATIONS

PART#	LENGTH	OUTSIDE DIAMETER	MATERIAL	FINISH	WEIGHT
R04664	36" TOTAL 30" IN-USE	1.6"	Aluminum	Safety Yellow Powder Coat	3.2 lbs



