

HD1QxxAN Series

High-Definition Interior Dome Camera

HD1Q High-Definition, Low-Profile Dome Camera

Capture the views you need, day or night with this high-resolution camera. Depend on the HD1Q camera series in a variety of lens options to fulfill all interior vehicle applications.



Works with DH4, DH4C, TH4, TH4C, TH6, TH8, NH16k and NH16 Recorders

■ Sharper Images Even in Low Light

Capture high-definition images in up to 720p resolution with infrared LEDs and WDR back light compensation for challenging light conditions.

■ Smaller Footprint

The low-profile dome housing allows for more discreet placement to better blend with vehicle decor.

■ Easy to Install

Simple plug and play installation with no complicated programming.

Key Features



720p progressive scan resolution



Low-profile, vandal-resistant housing



Infrared LEDs to see in low light



True Day/Night Operation



Back-light compensation improves image quality in high contrast conditions






High-fidelity audio

1.877.630.7366
safefleet.net

SAFE  FLEET
Driving Safety Forward™

HD1QxxAN Series

High-Definition Interior Dome Camera



Unless otherwise noted dimensions are in mm

Mechanical	
Enclosure Material	Solid aluminum alloy
Dome Material	Impact-resistant polycarbonate, anti-glare, scratch-resistant hardcoating, UV protected
Gimbal	Rotate: 360°, Pan: 360°, Tilt: 70° (assuming included Shim Kit is used)
Dimensions	95 x 67 mm
Weight	0.52 lbs (240g)
Optical	
Image sensor	1/3" CMOS 1.3MP
True Day/Night	IR cut filter
Shutter speed	Auto
Main Stream Resolution	720p (16:9 aspect ratio)
Electrical	
S/N ratio	>55dB
Camera sensitivity	Color: 0.1 lux (F2.0) B&W, IR LED on: 0 lux
Backlight Compensation	D-WDR On/off (OSD MENU)
IR	12 LEDs (5mm)
Power consumption	1 W (IR off); 2 W (IR on)
Voltage Range	12 VDC ± 10% (powered by DVR)
Transient Protection	1.5 kW
Environmental	
Environmental rating	IP54
Operational Temperature	-20 to 50°C (-4 to 122°F)

Available Lenses	
Focal length	H / V
03=2.8mm	89°/50°
04=3.6mm	65°/37°
06=6.0mm	44°/25°
Ordering Information	
HD1Q03AN	Mini Dome Interior Camera /w Audio, 720P, AHD, True D/N, IR, 2.8mm lens, White
HD1Q04AN	Mini Dome Interior Camera /w Audio, 720P, AHD, True D/N, IR, 3.6mm lens, White
HD1Q06AN	Mini Dome Interior Camera /w Audio, 720P, AHD, True D/N, IR, 6.0mm lens, White

Adding the suffix XX to the part number represents inclusion of a camera harness with the corresponding lengths as follows:
 20 = 20 ft
 50 = 50 ft
 75 = 75 ft

* IR LED's are permanently enabled to automatically turn ON or OFF depending on lighting conditions. IR LED's cannot be disabled

1410-HD1QxxAN-SS-ST-122123

Copyright ©2023 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

1.877.630.7366
safefleet.net

SAFE FLEET
Driving Safety Forward™