HD3U

High-Definition Ultra Wide Camera

Capture a wider field of view with sharper, more detailed images with this high-definition camera. See the full length of the bus for cross-view applications, capturing both the stepwell and driver view in a single view, day or night.



Works with all H-Series Recorders, except for TH4 and TH4C

Sharper Images even in Low Light

Capture high-definition images in 1080p resolution with 4 infrared LEDs, for challenging light conditions.

Small Footprint. Wide Views

This camera may be small in size, but delivers an ultra-wide 171° horizontal field of view of the full length of the vehicle interior.

Easy Install

Simple to install, aim and position, with no complicated programming or IP networking required.

Key Features



1080p progressive scan resolution



True Day/ Night Operation



Infrared LEDs to see in low light



High-fidelity audio



Ultra-Wide viewing angle

Mechanical/General	
Enclosure Material	Die-cast Aluminum (Powder-Coated)
Viewing Window	Polycarbonate
Bracket Material	SUS304
Dimensions (H x W x D)	Height 53.55mm; Width 68.60mm; Depth 63.74mm (with Bracket)
Weight (including bracket)	177g
Optical	
Image sensor	1/2.8" CMOS 2MP (1080P)
Lens	1.72mm (F2.0)
FOV	H:171, V:88
True Day/Night (TDN)	IR cut filter
Shutter speed	1/30 ~ 1/50,000
Resolution / Video Format	1080p 30fps* AHD 2.0 (16:9 aspect ratio) *TH6 supports a maximum of 15 fps
Electrical	
S/N ratio	≥ 46db (SNR1 lux: 0.23lx)
Camera Sensitivity	0 Lux (with IR) at TDN (B/W)
Backlight Compensation	DWDR
IR	4 LEDs 30ft distance
Power Consumption	IR Off = 1.4W, IR On = 4.2W
Voltage Range	9 to 14 VDC
Transient Protection	1.5 kW
Environmental	
Environmental Rating	IP67
Operating Temperature	-4 to 122°F (-20 to 50°C)

